


KIT interior, HD 720p

	Dome HD720p, 1/3" CMOS, IR 20m
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	1280(H) x 720(V)
Min. Illumination	0.01 Lux @ F1.2, AGC ON, 0 Lux with IR
Shutter Time	1/25s to 1/50.000s
Lens	3.6mm (2.8mm, 6mm optional)
	Angle of View: 76.88° (3.6mm), 99.73° (2.8mm), 50.1° (6mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	25 fps PAL
HD Video Output	1 Analog HD output
S/N Ratio	More than 52dB
Working Temperature	-40°C ~ +60°C
Working Humidity	Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	max. 3.5W
Weatherproof Ratings	IP66
IR Range	up to 20m
Dimensions	Ø 70 x 149.5mm
Weight	360g

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro



DVR TURBO HD 720p 4Ch

Video compression		H.264
Analog and HD-TVI video input		4-ch
		BNC interface, 1.0Vp-p, 75Ω
Supported camera types		720P25, 720P50, 1080P25, CVBS
Audio compression		G.711u
Audio input / Two-way audio IN		1-ch, RCA, 2.0 Vp-p, 1KΩ
HDMI / VGA output		1920x1080 / 60Hz, 1280x1024 / 60Hz, 1280x720 / 60Hz, 1024x768 / 60Hz
Encoding resolution	Main stream	1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF
	Sub-stream	WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame rate	Main stream	1/16 fps ~ Real time frame rate
	Sub-stream	1/16 fps ~ Real time frame rate
Video bitrate		32 Kbps - 6 Mbps
Audio output		1-ch, RCA, Linear, 1KΩ
Audio bitrate		64 Kbps
Dual-stream		Support
Stream type		Video, Video & Audio
Synchronous playback		4-ch
Playback resolution		1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Remote connections		128
Network protocols		TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Type		SATA interfaces
SATA		1 SATA interface
Capacity		Up to 4 Tb capacity for each disk
Network interface		1; 10M / 100M self-adaptive Ethernet interface
Serial interface		1; standard RS-485 serial interface, half-duplex
USB port		2 x USB2.0
Power supply		12 VDC
Consumption (without hard disks)		≤ 15W
Working temperature		-10°C ~ +55°C
Working humidity		10% ~ 90%
Chassis		1U chassis
Dimensions (W × D × H)		315 x 242 x 45mm
Weight (without hard disks)		≤ 1.5Kg

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro

	<p>Hard disk Western Digital 1 TB SATA3 64MB IntelliPower RPM</p>
	<p>Cablu UTP cat 5e</p>
	<p>Video balun pasiv economic, recomandat pentru transmisie 300m color/600m B/W, cablu 10cm</p>
	<p>Sursa AC 100~240V, DC 12V/5A;</p>
	<p>Instalare camere de supraveghere si traseu de cablu. Configurare DVR in functie de cerintele beneficiarului. Configurarea setari de retea pentru vizionare pe PC sau smartphone.</p>

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro